

T730 series SURFACE MOUNTED DOOR CLOSER

EN 1154 : 1997 Power Selectable EN 2~EN 4



Selectable Closing Force
Adjustable Closing & Latching Speeds
with Thermo-constant Valve
Non-Handed installation
Universal Application
Back check (Optional)

Outstanding Choice for General Commercial Application

The T730 series ideally suited for most common door in Architectural and Commercial applications.

• Features & Application

Selectable Closing Force

The force setting is altered by selecting position of closer on the door without changing existing fixing holes.

T73V	EN2	EN3	EN4
Max. Door Width (mm)	850	950	1100
Max. Door Weight (kgs)	40	60	80
Max. Opening Angle	180°	180°	180°

- One closer provides 3 different power sizes Save inventory cost
- Adjustable Closing & Latching Speed Thermo-constant Valve.
 Closing Speed Adjustable (140° ~ 10°)
 Adjustable Latching Action (10° ~ 0°)
- Non-handed Installation.
- OUniversal Application.
- OBackcheck beyond approx. 60°. (Optional)

Construction & Technical Details

- Onstructed with extruded anodized aluminum body, forged steel arm passively against rust & high quality steel internal components.
- © Cmpact design with minimized projection allowing installation to door having adjacent return wall at 90°
- OHeat treated steel rack & pinion immersed in high grade oil operate a nest of coils to give a smooth precise action & minimum wear.
- Piston & spindle been heat treated for high strength.
- ©Extra tensile strength alloy steel springs.
- OA built-in pressure relief valve protects the closer against rough use.
- Stable hydraulic fluid low sensitivity to temperature change
- Totally reversible without adjustment..

Certificates & Approvals

- Manufactured by quality assured ISO9001 factory.
- ©EN1154:1997 certified.
- © En1634: Part 1 & 3: 2000 certified.

Warranty - 1 years

Accessories

- Standard Arm => AR-A05, AR-A29
- O Hold Open Arm => AR-B09, AR-B31, AR-B33
- O Parallel Bracket => PA-H01
- Oprop Plate => MO-B01, MO-B02

Finishes

- O Satin Anodized Aluminum.
- O Polished Anodized Aluminum.
- Painted Sliver, Black, White, Brown & other RAL colors upon request & discuss.

Oimension

	Α	В	C	D	Е	F
T730	207	60	38.5	50	43	45

