

C6000 Series Concealed Door Closer

- . The Yale C6000 series Concealed Door Closer is recommended for use with interior doors only. Its slim aluminum body makes it suitable for thinner doors with minimum door thickness of 40mm in light duty applications.
- . This non-handed concealed door closer can be easily installed in the door or overhead in either wooden or steel doors
- The Yale C6000 series Concealed Door Closers can be easily adjusted to the desired closing speed by 2 adjusting valves in the body. The hold open angle can also be adjusted.
- · Internal components, such as steel rack, pinion, springs and spindle, are all heat-treated for extra strength and to give a smooth and precise action along with minimum wear for up to 500,000 cycles.
- · Available with two power sizes. Available with two power sizes conforming to EN2 and EN3.
- · Optional powder coat colors are also available on request.













Concealed Door Closer Product Specification


Product	Body								Sweeping Latch	Latching	g Max Angle of	Extreme	Arm Types				Additional features					Standard				
Decription	Material	L	w	н	L2	IJ	W3	Closing force	Max Door size	Mounting	Speed	Speed	Openning	Temperature	Adjustable	Hold-open	Parallel	Sliding	8C	CF	FC	DA	FO	UL	CEN	PSB
		П			П		Г														г	П	П	г		г
C6000	Aluminum	230	30	70	275	460	29	EN Size 2	800mm,40kg	Overhead	100° - 15°	15° - 0°	140°							•						
								EN Size 3	950mm,60kg	Door																

How to Order

C6000

C600	2	SB			
Series Name:	Closing Force:	Finish:			
	2 EN Size 2	BK Black			
	3 EN Size 3	BN Brown			
		GB Gold			
		SB Silver			

*Other paint color available upon request and negotiation



of products, reassures more people in more count ny other consumer locking solution.

THE ASSA ARLOY GROUP, is the world's leading manual

ASSA ARION An ASSA ABLOY Group brane