



Single Acting Door Accessories (Optional)



AB Accessories (Iron) (Adjustable)



Removable Spindle



A Accessories (Alum)

TYPE AND DOOR WEIGHT					
DC9400 TECHNICAL INFO. & FUNCTION		EN 2	EN 3	EN 4	
CLOSING FORCE (N · m) 0° - 4°		13-18	18-26	26-37	
WIDTH OF DOOR (mm) MAX		850	950	1100	
WEIGHT OF DOOR (Kg) MAX		40	60	80	
MAX OPEN ANGLE		130°			
HOLD-OPEN		90° or 105°			
CLOSING SPEED ADJUSTMENT	SPEED 1	90° to 15°			
	SPEED 2	15° to 0°			
REMOVABLE SPINDLE		Optional			
APPLICABLE TEMPERATURE		-30°C to 45°C			
APPLICABILITY		Wooden, glass & aluminium door etc. Left-open, right-open, single-side open or both-side open.			
WEIGHT(kg)		5.1	5.2	5.3	
DIMENSION OF CEMENT BOX(mm)	LENGTH	305			
	WIDTH	108			
	HEIGHT	40.5			
PASSED DURABILITY TEST		500,000 cycles			

FEATURES

- * Suitable for wooden, glass and aluminium doors
- * Max opening angle in each direction:130°
- * Inside the frame: Height can be adjusted within 4 mm. Width can be adjusted within 5mm between left and right length can be adjusted within 7mm
- * Proven, robust unit for door weights up to 120 kg.

Yale Model No.	Description
DC9400-EN2	Floor Closer (with stainless-steel cover plate)
DC9400-EN3	Floor Closer (with stainless-steel cover plate)
DC9400-EN4	Floor Closer (with stainless-steel cover plate)
DC9400-EN2-RS	Floor Closer with Removable Spindle (with stainless-steel cover plate)
DC9400-EN3-RS	Floor Closer with Removable Spindle (with stainless-steel cover plate)
DC9400-EN4-RS	Floor Closer with Removable Spindle (with stainless-steel cover plate)
DC-A-RS10	Accessories - Removal Spindle 10 mm
DC-A-RS20	Accessories - Removal Spindle 20 mm
DC-A-T&B A	Accessories - Top Pivot & Bottom Arm (Alum)
DC-A-T&B I-A	Accessories - Top Pivot & Bottom Arm (Iron - Adjustable)
DC-A-T&B I-SA	Accessories - Top Pivot & Bottom Arm (Iron - Single Action)

Standard Configuration: Standard Floor Closer packed with AB Accessories (Iron) with Non-Hold-open function. Please specify different accessories type and / or Hold-Open degree when required.