



Single Acting Door Accessories (Optional)



AB Accessories (Iron) (Adjustable)



Removable Spindle



A Accessories (Alum)

TYPE AND DOOR WEIGHT					
DC9500 TECHNICAL INFO. & FUNCTION		EN 2	EN 3	EN 4	
CLOSING FORCE (N · m) 0° - 4°		13-18	18-26	26-37	
WIDTH OF DOOR (mm) MAX		850	950	1100	
WEIGHT OF DOOR (Kg) MAX		40	60	80	
MAX OPEN ANGLE		180°			
HOLD-OPEN		90° or 130° to 180° Random hold-open			
CLOSING SPEED	SPEED 1	90° to 15°			
ADJUSTMENT	SPEED 2	15° to 0°			
REMOVABLE SPINDLE		Optional			
APPLICABLE TEMPERATURE		-30°C to 45°C			
APPLICABILITY		Wooden, glass & aluminium door etc. Left-open, right-open, single-side open or both-side open.			
WEIGHT(kg)		4.1	4.2	4.3	
DIMENSION OF CEMENT BOX(mm)	LENGTH	265			
	WIDTH	85			
	HEIGHT	50.5			
PASSED DURABILITY TEST		500,000 cycles			

Yale Model No.	Description	
DC9500-EN2	Floor Closer (with stainless-steel cover plate)	
DC9500-EN3	Floor Closer (with stainless-steel cover plate)	
DC9500-EN4	Floor Closer (with stainless-steel cover plate)	
DC9500-EN2-RS	Floor Closer with Removable Spindle (with stainless-steel cover plate)	
DC9500-EN3-RS	Floor Closer with Removable Spindle (with stainless-steel cover plate)	
DC9500-EN4-RS	Floor Closer with Removable Spindle (with stainless-steel cover plate)	
DC-A-RS10	Accessories - Removal Spindle 10 mm	
DC-A-RS20	Accessories - Removal Spindle 20 mm	
DC-A-T&B A	Accessories - Top Pivot & Bottom Arm (Alum)	
DC-A-T&B I-A	Accessories - Top Pivot & Bottom Arm (Iron - Adjustable)	
DC-A-T&B I-SA	Accessories - Top Pivot & Bottom Arm (Iron - Single Action)	

FEATURES

- * Easy installation of universal design, suitable for left and right opening & single-door and double-door two direction opening.
- ★ Easy to adapt to individual requirements with dual valve, according to different requirment to adjust closing speed and latching force, also available with different door closer for special requirement.
- * Inside the frame:
 Height can be
 adjusted within 4
 mm.Width can be
 adjusted within 5 mm
 between left and right
 length can be
 adjusted within
 10 mm.
- Proven, robust unit for door weights up to 120 kg.

Standard Configuration: Standard Floor Closer packed with AB Accessories (Iron) with Non-Hold-open function. Please specify different accessories type and / or Hold-Open degree when required.