

C2000

Technical features:

- brass body
- brass plugs
- self-lubricating sintered steel projecting cam, DIN-compatible
- pins:
 - in brass
 - in hardened steel in first position
- drivers:
 - in brass
 - in hardened steel in first position
- phosphor bronze springs
- KEY:
- nickel-plated brass
- long key for protective roses compatibility
- numerical coding on the head

Supplied as standard:


- 3 keys
- Fixing screw




Finishes:

- STANDARD:
 - sanded brass (fin. 00)
- ON REQUEST:
 - nickel-plated brass (fin. 12)
 - polished brass (66)

Standards:

- Compliant with EN 1303:2005
- Attack Resistance: grade 0
- Key Related Security: grade 4
- Durability: grade 6

Type	Description	Comm. dim.				Key item	Kg	Pieces	ITEM				
		L	A	B	Pins				Type	Dim.	Hand	Fin.	Spec.
	• Double cylinder	22 / 22	43,4	21,7	21,7	3	1 01070 01 1	0,172	12	1	OG300	02 0	
		22 / 27	48,4	21,7	26,7	3	1 01070 01 1	0,192	12	1	OG300	03 0	
		25 / 25	49,8	24,9	24,9	4	1 01070 05 1	0,189	12	1	OG300	04 0	
		27 / 27	53,0	26,5	26,5	4	1 01070 05 1	0,200	12	1	OG300	05 0	
		27 / 33	59,0	26,5	32,5	4	1 01070 05 1	0,216	12	1	OG300	06 0	
		30 / 30	59,0	29,5	29,5	5	1 01070 10 1	0,216	12	1	OG300	07 0	
		30 / 33	62,0	29,5	32,5	5	1 01070 10 1	0,212	12	1	OG300	08 0	
		27 / 37	63,0	26,5	36,5	4	1 01070 05 1	0,237	12	1	OG300	09 0	
		30 / 35	64,0	29,5	34,5	5	1 01070 10 1	0,233	12	1	OG300	26 0	
		33 / 33	65,0	32,5	32,5	5	1 01070 10 1	0,233	12	1	OG300	10 0	
		27 / 43	69,0	26,5	42,5	4	1 01070 05 1	0,250	12	1	OG300	11 0	
		30 / 40	69,0	29,5	39,5	5	1 01070 10 1	0,250	12	1	OG300	12 0	
		35 / 35	69,0	34,5	34,5	5	1 01070 10 1	0,250	12	1	OG300	13 0	
		30 / 43	72,0	29,5	42,5	5	1 01070 10 1	0,258	6	1	OG300	14 0	
		37 / 37	73,0	36,5	36,5	5	1 01070 10 1	0,266	6	1	OG300	15 0	
		30 / 45	74,0	29,5	44,5	5	1 01070 10 1	0,266	6	1	OG300	27 0	
		35 / 40	74,0	34,5	39,5	5	1 01070 10 1	0,266	6	1	OG300	28 0	
		27 / 53	79,0	26,5	52,5	4	1 01070 05 1	0,283	6	1	OG300	16 0	
		30 / 50	79,0	29,5	49,5	5	1 01070 10 1	0,291	6	1	OG300	17 0	
		35 / 45	79,0	34,5	44,5	5	1 01070 10 1	0,283	6	1	OG300	19 0	
		40 / 40	79,0	39,5	39,5	5	1 01070 10 1	0,285	6	1	OG300	18 0	
		30 / 55	84,0	29,5	54,5	5	1 01070 10 1	0,300	6	1	OG300	33 0	
		35 / 50	84,0	34,5	49,5	5	1 01070 10 1	0,300	6	1	OG300	31 0	
		40 / 45	84,0	39,5	44,5	5	1 01070 10 1	0,300	6	1	OG300	30 0	
		43 / 43	85,0	42,5	42,5	5	1 01070 10 1	0,303	6	1	OG300	46 0	
		30 / 60	89,0	29,5	59,5	5	1 01070 10 1	0,316	6	1	OG300	20 0	
		35 / 55	89,0	34,5	54,5	5	1 01070 10 1	0,325	6	1	OG300	32 0	
		40 / 50	89,0	39,5	49,5	5	1 01070 10 1	0,316	6	1	OG300	21 0	
		45 / 45	89,0	44,5	44,5	5	1 01070 10 1	0,325	6	1	OG300	29 0	
		35 / 60	94,0	34,5	59,5	5	1 01070 10 1	0,312	6	1	OG300	38 0	
		45 / 50	94,0	44,5	49,5	5	1 01070 10 1	0,312	6	1	OG300	39 0	
		40 / 55	94,0	39,5	54,5	5	1 01070 10 1	0,330	6	1	OG300	42 0	
		30 / 65	94,0	29,5	64,5	5	1 01070 10 1	0,350	6	1	OG300	41 0	
		30 / 70	99,0	29,5	69,5	5	1 01070 10 1	0,350	6	1	OG300	24 0	
		35 / 65	99,0	34,5	64,5	5	1 01070 10 1	0,312	6	1	OG300	22 0	
		40 / 60	99,0	39,5	59,5	5	1 01070 10 1	0,350	6	1	OG300	25 0	
		45 / 55	99,0	44,5	54,5	5	1 01070 10 1	0,312	6	1	OG300	43 0	
		50 / 50	99,0	49,5	49,5	5	1 01070 10 1	0,350	6	1	OG300	23 0	
		45 / 60	104,0	44,5	59,5	5	1 01070 10 1	0,350	6	1	OG300	54 0	
		35 / 70	104,0	34,5	69,5	5	1 01070 10 1	0,350	6	1	OG300	49 0	
		30 / 80	109,0	29,5	79,5	5	1 01070 10 1	0,350	6	1	OG300	37 0	
		40 / 70	109,0	39,5	69,5	5	1 01070 10 1	0,360	6	1	OG300	35 0	
		50 / 60	109,0	49,5	59,5	5	1 01070 10 1	0,360	6	1	OG300	36 0	
		55 / 55	109,0	54,5	54,5	5	1 01070 10 1	0,360	6	1	OG300	70 0	
		60 / 60	119,0	59,5	59,5	5	1 01070 10 1	0,390	6	1	OG300	40 0	
		30 / 90	119,0	29,5	89,5	5	1 01070 10 1	0,390	6	1	OG300	52 0	
		40 / 80	119,0	39,5	79,5	5	1 01070 10 1	0,390	6	1	OG300	60 0	
		70 / 70	139,0	69,5	69,5	5	1 01070 10 1	0,440	6	1	OG300	50 0	

Type	Description	Comm. dim.	Key item				Kg	Unit weight	Pieces	ITEM			
			L	A	B	Pins				Type	Dim.	Hand	Pers. Spec.
	• Clutching system double cylinder	27 / 27	53,0	26,5	26,5	4	1 01070 05 1	0,202	12	1	OG301	05 0	
		27 / 33	59,0	26,5	32,5	4	1 01070 05 1	0,222	12	1	OG301	06 0	
		30 / 30	59,0	29,5	29,5	5	1 01070 10 1	0,222	12	1	OG301	07 0	
		27 / 37	63,0	26,5	36,5	4	1 01070 05 1	0,232	12	1	OG301	09 0	
		30 / 35	64,0	29,5	34,5	5	1 01070 10 1	0,232	12	1	OG301	26 0	
		27 / 43	69,0	26,5	42,5	4	1 01070 05 1	0,252	12	1	OG301	11 0	
		35 / 35	69,0	34,5	34,5	5	1 01070 10 1	0,252	12	1	OG301	13 0	
		30 / 40	69,0	29,5	39,5	5	1 01070 10 1	0,252	12	1	OG301	12 0	
		35 / 40	74,0	34,5	39,5	5	1 01070 10 1	0,252	12	1	OG301	28 0	
		40 / 45	84,0	39,5	44,5	5	1 01070 10 1	0,252	12	1	OG301	30 0	
	• Single cylinder with adjustable cam in 8 position	25 / 10	34,5	24,5	10,0	4	1 01070 05 1	0,146	12	1	OG304	18 0	
		30 / 10	39,5	29,5	10,0	5	1 01070 10 1	0,155	12	1	OG304	02 0	
		33 / 10	42,5	32,5	10,0	5	1 01070 10 1	0,165	12	1	OG304	09 0	
		35 / 10	44,5	34,5	10,0	5	1 01070 10 1	0,170	12	1	OG304	07 0	
		37 / 10	46,5	36,5	10,0	5	1 01070 10 1	0,175	12	1	OG304	10 0	
		40 / 10	49,5	39,5	10,0	5	1 01070 10 1	0,191	12	1	OG304	03 0	
		43 / 10	52,5	42,5	10,0	5	1 01070 10 1	0,195	12	1	OG304	11 0	
		50 / 10	59,5	49,5	10,0	5	1 01070 10 1	0,215	12	1	OG304	04 0	
		55 / 10	64,5	54,5	10,0	5	1 01070 10 1	0,245	12	1	OG304	35 0	
		60 / 10	69,5	59,5	10,0	5	1 01070 10 1	0,245	12	1	OG304	05 0	
		64 / 10	73,5	63,5	10,0	5	1 01070 10 1	0,255	12	1	OG304	21 0	
		70 / 10	79,5	69,5	10,0	5	1 01070 10 1	0,275	12	1	OG304	06 0	
		80 / 10	89,5	79,5	10,0	5	1 01070 10 1	0,305	12	1	OG304	20 0	
		94 / 10	103,5	93,5	10,0	5	1 01070 10 1	0,355	12	1	OG304	13 0	
	• Double cylinder with thumb turn shaft • ON REQUEST: Knobs series 06353, 06354, 06355, 06356, 06357	30 / 30	59,0	29,5	29,5	5	1 01070 10 1	0,237	6	1	OG302	07 0	
		30 / 35	64,0	29,5	34,5	5	1 01070 10 1	0,250	6	1	OG302	26 0	
		35 / 30	64,0	34,5	29,5	5	1 01070 10 1	0,250	6	1	OG302	81 0	
		33 / 33	65,0	32,5	32,5	5	1 01070 10 1	0,255	6	1	OG302	10 0	
		30 / 40	69,0	29,5	39,5	5	1 01070 10 1	0,270	6	1	OG302	82 0	
		35 / 35	69,0	34,5	34,5	5	1 01070 10 1	0,270	6	1	OG302	13 0	
		40 / 30	69,0	39,5	29,5	5	1 01070 10 1	0,270	6	1	OG302	12 0	
		35 / 40	74,0	34,5	39,5	5	1 01070 10 1	0,285	6	1	OG302	28 0	
		40 / 35	74,0	39,5	34,5	5	1 01070 10 1	0,285	6	1	OG302	83 0	
		30 / 50	79,0	29,5	49,5	5	1 01070 10 1	0,300	6	1	OG302	17 0	
		35 / 45	79,0	34,5	44,5	5	1 01070 10 1	0,300	6	1	OG302	19 0	
		40 / 40	79,0	39,5	39,5	5	1 01070 10 1	0,300	6	1	OG302	18 0	
		45 / 35	79,0	44,5	34,5	5	1 01070 10 1	0,300	6	1	OG302	85 0	
		40 / 45	84,0	39,5	44,5	5	1 01070 10 1	0,315	6	1	OG302	30 0	
		45 / 40	84,0	44,5	39,5	5	1 01070 10 1	0,315	6	1	OG302	84 0	
		43 / 43	85,0	42,5	42,5	5	1 01070 10 1	0,318	6	1	OG302	46 0	
		30 / 60	89,0	29,5	59,5	5	1 01070 10 1	0,330	6	1	OG302	20 0	
		40 / 50	89,0	39,5	49,5	5	1 01070 10 1	0,330	6	1	OG302	21 0	
		45 / 45	89,0	44,5	44,5	5	1 01070 10 1	0,330	6	1	OG302	29 0	
		40 / 55	94,0	39,5	54,5	5	1 01070 10 1	0,350	6	1	OG302	42 0	
		45 / 50	94,0	44,5	49,5	5	1 01070 10 1	0,350	6	1	OG302	39 0	
		45 / 55	99,0	44,5	54,5	5	1 01070 10 1	0,360	6	1	OG302	43 0	
		50 / 50	99,0	49,5	49,5	5	1 01070 10 1	0,360	6	1	OG302	23 0	
		45 / 60	104,0	44,5	59,5	5	1 01070 10 1	0,375	6	1	OG302	54 0	
		55 / 50	104,0	54,5	49,5	5	1 01070 10 1	0,375	6	1	OG302	64 0	
		30 / 80	109,0	29,5	79,5	5	1 01070 10 1	0,390	6	1	OG302	37 0	
		40 / 70	109,0	39,5	69,5	5	1 01070 10 1	0,390	6	1	OG302	35 0	
		50 / 60	109,0	49,5	59,5	5	1 01070 10 1	0,390	6	1	OG302	36 0	
		60 / 50	109,0	59,5	49,5	5	1 01070 10 1	0,390	6	1	OG302	89 0	
		55 / 60	114,0	54,5	59,5	5	1 01070 10 1	0,400	6	1	OG302	71 0	
		55 / 65	119,0	54,5	64,5	5	1 01070 10 1	0,420	6	1	OG302	72 0	
		60 / 60	119,0	59,5	59,5	5	1 01070 10 1	0,420	6	1	OG302	40 0	
		65 / 55	119,0	64,5	54,5	5	1 01070 10 1	0,420	6	1	OG302	86 0	