Oval Profile Mortice



Oval Profile Mortice Night Latch

2341/L2341

Application:

- · For timber doors hinged on the left or right
- Also suitable for steel & composite doors special fixings required

Operation:

- Latch bolt withdrawn by oval cylinder from outside and sprung lever handle or separate turn from inside
- Latch bolt is held in the withdrawn position by use of special key supplied (7126-30)
- · Reversible latch bolt
- · Cylinder options single cylinder or key and key
- Latch bolt is automatically locked against end pressure by the anti-thrust bolt
- · 2341 supplied with 2X8 cylinder

Specification:

Reference L2341 (lock case & strike plate)

Case Size 77.5mm (3") Backset 57mm

Case Steel, silver powder coat
Outer Forend Stainless steel or brass
Striking Plate Finished to match forend

Deadbolt n/a

Latch Bolt Brass, reversible Follower Steel, 8mm square

Rebate Kit 2942 (13mm, 19mm or 25mm)

Cylinder Type 2341 supplied with 2X8 cylinder

L2341 oval profile (not supplied)



Finishes:

- · SC Satin Chrome finish
- · PL Polished Brass finish

Standards:



 EN 1634-1 assessed for use on 60 minutes timber fire doors

Ordering Code Example:

J L2341 - PL - 3.00 (case & strike plate)

J 2341 - PL - 3.00 (complete with 2X8 cylinder)

(Boxed - Product Code - Finish - Case Size)

Features:

- · Reversible latch bolt
- · Available with square forend and striking plate

